

## COLORBOND® Metallic prepainted steel

### INTRODUCTION

COLORBOND® Metallic prepainted steel offers a range of decorative finishes which are ideal for prestigious building applications.

Due to the unique nature of pearlescent finishes, as used on COLORBOND® Metallic steel, certain precautions are necessary when ordering and installing this product.

### GEOMETRIC METAMERISM

The metallic type paint systems obtain their unique lustre from the addition of mica pigments to the paint. These pigments, whilst being responsible for the unique appearance, also result in a visual effect known as geometric metamerism.

Geometric metamerism is a phenomenon where the colour of the painted surface will appear to be different dependant upon viewing angles and lighting conditions.

In order to highlight this effect, *Figure 1* shows a disc punched from a sample of COLORBOND® Metallic steel in the colour Skybridge® which has been rotated through 45°, 90° and 180°. As the figure illustrates, when the same material is rotated relative to its original orientation, a significant inherent difference in colour and appearance can be observed.


### ORDERING

Due to the sensitive nature of these paint systems, different batches of product may vary slightly in appearance.

In order to minimise appearance differences it is strongly recommended that all requirements for a particular project are processed in one production run using the same batch of paint. The customer should inform the BlueScope Steel Limited Sales Office of all COLORBOND® Metallic steel requirements for a given project so the orders can be batched.

Notifying the BlueScope Steel Sales Office is particularly important when a project calls for various sizes to avoid material being supplied from different batches.

Figure 1: The effect of metamerism due to rotation of samples



Material will be of consistent appearance when painted in the one production run using the same batch of paint.

### ROLLFORMING

Rollformed sections of COLORBOND® Metallic steel often display striking effects due to the varying angles of incident light.

The customer should be aware of this visual effect as well as the potential for variation between vertical and horizontal exposure. Accessories will be subject to different conditions of incident lighting compared to flat roof or wall panels.

### INSTALLATION

In order to prevent mismatching, all panels on a project should be aligned in the same direction.

To assist in this regard, BlueScope Steel brands the reverse surface of all COLORBOND® Metallic steel with an arrow to indicate the direction of painting.

However, when fabricating architectural panels the arrow indicating direction of painting is no longer visible. Care should be taken to ensure that a suitable system exists to convey this information to the installer.

Caution must also be taken during installation to ensure that adjacent panels fit flush and flat relative to one another. Failure to do so will again result in appearance variations.

“Touching up” minor surface scratches on COLORBOND® Metallic steel is not recommended. Minor scratching will not affect the life of the product and is rarely obvious to the casual observer. If the surface scratching is severe the material should be replaced.

### ACCESSORIES

It should be noted that any accessories, such as gutter clips, which are not made from COLORBOND® Metallic steel, will be subject to a metamerism effect and as a result are likely to be different in appearance. This is due to the differences in paint chemistry and method of paint application between COLORBOND® Metallic steel and post-painted or powder coated accessory items.

### SUMMARY

1. Order all material for one project at the same time.
2. Install panels according to painting direction and ensure they fit flush and flat relative to one another.
3. Do not mix material produced from different paintline runs.
4. Be aware of the unique visual effects on rollformed sections and horizontal versus vertical exposure.

**If you have any questions regarding this Bulletin, please contact BlueScope Steel Direct on 1800 800 789.**

**To ensure you have the most current Technical Bulletin, please go to [bluescopesteel.com.au](http://bluescopesteel.com.au).**



The information and advice contained in this Technical Bulletin ('Bulletin') is of a general nature only and has not been prepared with your specific needs in mind. You should always obtain specialist advice to ensure that the materials, approach and techniques referred to in this Bulletin meet your specific requirements.

BlueScope Steel Limited makes no warranty as to the accuracy, completeness or reliability of any estimates, opinions or other information contained in this Bulletin and to the maximum extent permitted by law, BlueScope Steel Limited disclaims all liability and responsibility for any loss or damage, direct or indirect, which may be suffered by any person acting in reliance on anything contained in or omitted from this Bulletin.

COLORBOND®, BlueScope and ® colour names are registered trade marks of BlueScope Steel Limited. ™ colour names are trade marks of BlueScope Steel Limited.

© 2014 BlueScope Steel Limited ABN 16 000 011 058. BlueScope Steel (AIS) Pty Ltd ABN 19 000 019 625. All rights reserved.

